

DCE-S 6/8 Plus

PRODUCT-NO.: 238153

Enjoy reliable heat Life has its ups and downs. So we think it's reassuring to have a hot water supply in your home that you can always count on. With this compact instantaneous water heater, water at a pleasant temperature is a given. With efficiency that is second to none. Very easy to operate With its minimal dimensions yet powerful output, this appliance supplies either several hand washbasins or a shower with water at your preferred temperature. Thanks to the rotary selector, it's easy to make adjustments. The end result is reliable hot water as an integral part of your day.



The main features

Electronically controlled compact instantaneous water heater

Very good energy efficiency thanks to 3i technology

Precise temperature selection from 20 °C to 60 °C

Permanently selectable temperature limit can be set to 43 °C, 50 °C or 55 °C

Suitable for showers

Exceptionally slimline, compact design







Туре	DCE-S 6/8 Plus	DCE-S 10/12 Plus
Part no.	238153	238154
Technical data		
Rated voltage	220 V	220 V
Rated voltage 1	220 V	220 V
Rated voltage 2	230 V	230 V
Rated voltage 3	240 V	240 V
Rated output	6.0/8.0 kW	10.0/12.0 kW
Rated output 1	6.0/8.0 kW	10.0/12.0 kW
Rated output 2	6.6/8.7 kW	11.0/13.1 kW
Rated output 3	7.2/9.6 kW	12.0/14.3 kW
Rated current	27.3/36.4 A	45.5/54.5 A
Rated current 1	27.3/36.4 A	45.5/54.5 A
Rated current 2	28.5/38.0 A	47.8/57.0 A
Rated current 3	30.0/40.0 A	50.0/59.5 A
Fuse protection	30/40 A	50/60 A
Fuse protection 1	30/40 A	50/60 A
Fuse protection 2	30/40 A	50/60 A
Fuse protection 3	30/40 A	50/60 A
Frequency	50/60 Hz	50/60 Hz
Frequency 1	50/60 Hz	50/60 Hz
Frequency 2	50/60 Hz	50/60 Hz
Frequency 3	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE
Resistivity ρ15 ≥	1100 Ω cm	1100 Ω cm



Conductivity σ15 ≤	910 μS/cm	910 μS/cm
IP rating	IP 25	IP 25
Temperature setting	20-60 °C	20-60 °C
Colour	white	white
ON	1.3 l/min	1.3 l/min
Height	372 mm	372 mm
Width	217 mm	217 mm
Depth	109 mm	109 mm
Weight	2.50 kg	2.50 kg